

Quick Start Guide

Messenger BLE

1. Basic Messenger BLE Kit

The basic Messenger BLE kit includes one of each:

Part Numbers vary by data provider

A	Messenger BLE	
B	Cable – MG BLE to 6P	1800-0030
C	Harness – D21 to D21 with 6P dropout	812-7760-32
D	Antenna – GPS mag mount	1300-0019
E	Antenna Kit – 5dbi external mount with 10 ft	5000-0023

Data Plans:

1. AT&T 5000-0083
2. Verizon 5000-0084



A



B



C



D



E



Quick Start Guide

Messenger BLE

2. Telemetry Communications

The basic Messenger BLE kit provides power and CANbus to the device, cellular communications and GPS location allowing for remote monitoring and start/stop with throttle control via RemotelQ.

This basic kit does not provide access to Messenger BLE I/O. Additional accessories and harnessing are required to utilize telemetry I/O.




Quick Start Guide

Messenger BLE


4. Part # 2HAR-9221-A001

This harness connects to JR2 and provides access to Power and CANBus, Analog Input 1, Modbus, and Digital Input 1.



5. Part # 2HAR-9221-A101

This harness connects to JR2 and provides access to Power and CANBus, and Analog Input 1.



Parameters for accessories connected to the Messenger BLE will be displayed in RemotelQ™ but not on the pump panel display screen.



Quick Start Guide


Messenger BLE

6. Data Plans

If you purchased a data plan with the hardware, your device arrives activated and ready to use. If you have the hardware and need to activate service, please contact Support.Antx@cattron.com or call 877.399.2937.

1. Using a QR Code Scanning App*, scan the QR code on the Messenger BLE device to access all device identification information.

* iPhone cameras will not scan the QR code.



7. Accessories

For connection to the Messenger BLE, not the panel

1800-0072	Cable – M12 M/F, 5Pin, 6 meter
503-1652-24	Pressure Transducer – 0-100psi, 4-20mA, 10x over pressure, .5% accuracy, 1/4" NPT male
503-1652-06	Pressure Transducer – 0-200psi, 4-20mA, 10x over pressure, .5% accuracy, 1/4" NPT male
503-1652-33	Pressure Transducer – 0-500psi, 4-20mA, 10x over pressure, .5% accuracy, 1/4" NPT male
503-1650-10	Vacuum Transducer – 14.7-200psi, 4-20mA, 10x over pressure, .5% accuracy, 1/4" NPT male
5000-0056	Armored Level Transducer Kit – 10psi, cables: 40' wet, 35' dry
5000-0019	Solar Battery Charger – 10W, 12V, direct connect
5000-0015	Solar Battery Charger – 40W, 12V, integrated charge, ring terminal and alligator clip extensions
Flow Meters – size 2" and up, 4-20mA, pulse and Modbus options. Power and communication cables	

